



|                                      |                                                  |
|--------------------------------------|--------------------------------------------------|
| Installation                         | Pendant                                          |
| Power Consumption ( +-5% )           | 150 W                                            |
| LED Module                           | Lumileds ( Philips ) SMD                         |
| Luminous Flux                        | 21,000 lm                                        |
| Luminor Efficiency                   | 140 lm/W                                         |
| CCT ( Correlated Color Temperature ) | 3000-6000 K                                      |
| CRI ( Color Rendering Index )        | >70 / >80                                        |
| Beam Angle                           | 70° / 85° / 110° - 0% / 10% / 20% Up Light       |
| Reflection Type                      | Optical Lens                                     |
| Input Voltage                        | 95-265 V                                         |
| Driver                               | MeanWell                                         |
| Power Factor                         | >95                                              |
| Ambient Temperature Range            | -40°~45°                                         |
| Dimming Protocol ( Optional )        | Dali / 0-10V / PWM / Zigbee                      |
| Mech.Impact Protection Code          | IK08                                             |
| Ingress Protection Code              | IP65                                             |
| Optional Accesories                  | Optional - Light Sensor / Motion Sensor / Zigbee |
| Lifespan                             | >50,000 Hours                                    |
| Color                                | Black / White                                    |
| Weight                               | 6 KG                                             |
| Dimensions                           | 350x273 mm                                       |