



|                                      |                                                                           |
|--------------------------------------|---------------------------------------------------------------------------|
| Installation                         | Surface Mounted                                                           |
| Power Consumption ( +-5% )           | 640 W                                                                     |
| LED Modul                            | Philips / Samsung / Osram                                                 |
| Luminous Flux                        | 75,000 lm                                                                 |
| Luminor Efficiency                   | 120 lm/W                                                                  |
| CCT ( Correlated Color Temperature ) | 3000-6000 K                                                               |
| CRI ( Color Rendering Index )        | >70 / 80 / 90                                                             |
| Light Color                          | White / Warm White / Cool White / Red / Green / Blue / Amber / RGB / RGBW |
| Beam Angle                           | 12° / 30° / 60° / 135°x60° / 135°x85°                                     |
| Reflection Type                      | Optical Lens                                                              |
| Input Voltage                        | 95-265 V                                                                  |
| Driver                               | MeanWell                                                                  |
| Power Factor                         | >95                                                                       |
| Ambient Temperature Range            | -30°~+40°                                                                 |
| Dimming                              | Optional                                                                  |
| Mech.Impact Protection Code          | IK08                                                                      |
| Ingress Protection Code              | IP65                                                                      |
| Control Protocol                     | Optional - DMX / Dali                                                     |
| LED Lifespan                         | > 60,000 Hours                                                            |
| Weight                               | 28.5 KG                                                                   |
| Dimensions                           | 685x712x100 mm                                                            |